



# High Performance Cooled CCD Camera System ASCENT® A1050

The Ascent A1050 has a 1-megapixel interline transfer sensor with low noise and high quantum efficiency. The camera is available with a monochrome (A1050) or color (A1050C) sensor. Small pixels are ideal for microscopy.

- 1024 x 1024 array, 5.5 x 5.5 micron pixels
- 32 Mbyte SDRAM image buffer
- Programmable 16-bit digitization speeds up to 16 Mpixels/sec
- Single or dual channel readout
- Video focus mode
- USB 2.0 interface: no plug in cards or external controllers
- Programmable, intelligent cooling to 35°C below ambient
- Binning up to 8 Horizontal x 1024 Vertical
- Subarray readout and fast sequencing modes
- Programmable offset and gain
- External triggering and strobe controls
- ActiveX drivers included with every system
- Field upgradeable firmware
- Fused silica window
- Optional C-mount, Nikon F-mount, or 2" slip fit adapter
- Optional 6-position 1"/25mm or 8-position 1.25"/31mm filter wheel
- Single 6V supply
- Compact enclosure: 20 oz. (0.57 kg)

- Chemiluminescence
- Fluorescence
- Astronomy
- Colorimetry

■  
Imaging Area of CCD



## CCD SPECIFICATIONS (from CCD manufacturer)

CCD	KAI-1050
Array Size (pixels)	1024 x 1024
Pixel Size	5.5 x 5.5 microns
Imaging Area	5.6 x 5.6 mm (31.7 mm <sup>2</sup> )
Imaging Diagonal	8 mm
Video Imager Size	0.5"
Linear Full Well (typical)	20K electrons
Dynamic Range	64 dB
QE at 400 nm (mono)	32%
Peak QE (500 nm)	50%
Anti-blooming (nominal)	300X



For complete CCD specifications, including cosmetic grading, see data sheet from manufacturer.

Part Numbers	
A1050 (mono)	A1D-01050MS-FS
A1050C (color)	A1D-01050CS-FS



151 N. Sunrise Ave. Ste 902  
Roseville CA 95661 USA  
tel 916 218 7450  
fax 916 218 7451  
www.ccd.com

PC Interface	USB 2.0
USB2 Cable	Std.: 5m. Extensions: 5 meters between hubs; 5 hubs maximum (max. total of 30m) Wide variety of extenders available, including fiber optics to 10 km.
Digital Resolution	16 bits: 3.3 and 8 Mpixels/sec (single channel); 16 Mpixels/sec (dual 8 MHz) (software selectable)
System Noise (typical)	6 e <sup>-</sup> RMS at 3.3 MHz; 7 e <sup>-</sup> RMS at 8/16 MHz
Pixel Binning	1 x 1 to 8 x 1024 on-chip
Exposure Time	Minimum 100 microseconds (no vane shutter); max. 183 minutes
Image Sequencing	1 to 65535 image sequences under software control
Frame Sizes	Full frame, subframe, focus mode
Cooling (typical)	Thermoelectric cooler. Maximum forced air cooling 35°C below ambient temperature.
Dark Current (typical)	0.01 eps (-10°C)
Temperature Stability	± 0.1°C
Camera Head Size	Aluminum. 3.2" x 4.7" x 1.3" (8.1 x 11.9 x 3.3 cm) Weight: 1.25 lb. (0.57 kg)
Mounting	1.5" x 2.5" bolt pattern, 6-32 thread. Optional C-mount (1" 32 tpi thread), Nikon F-mount, or 2" slip-fit adapters.
Back Focal Distance	Standard: 0.32" (0.81 cm). [optical]
Operating Environment	-30°C to 35°C. Relative humidity: 10 to 90% non-condensing.
Op.Sys.Support	Windows, Linux, Mac OSX
Power	20W maximum power with internal shutter open and cooling maximum. AC/DC "brick" supply with int'l AC input plug (100-240V, 50-60 Hz). Alternate 6V input from user's source.
Remote Triggering	LVTTL input allows exposure to start within 25 microseconds of rising edge of trigger

### CCD SENSITIVITY

