



Alta[®] U260

High Performance Cooled CCD Camera System



The Alta U260 has a Kodak Blue Plus full-frame sensor with high quantum efficiency. Its very high dynamic range is ideal for OEMs, biological sciences, spectroscopy and astronomy.

- 512 x 512 array, 20 x 20 micron pixels
- 5 MHz 12-bit and 1 MHz 16-bit digitization (High output)
- 32Mbyte camera memory
- USB 2.0 interface: no plug in cards or external controllers
- Programmable, intelligent cooling to 50C below ambient
- Binning up to 10 Horizontal x 512 Vertical
- Subarray readout and fast sequencing modes
- Precision time delayed integration readout
- Programmable fan speed for low / zero vibration
- Two serial port outputs for control of peripheral devices
- General purpose programmable I/O port
- External triggering and strobe controls
- ActiveX drivers and MaxIm DL/CCD software included with every system
- Field upgradeable firmware
- Self-test capability with data simulators
- Fused silica windows
- Runs from single 12V supply with input voltage monitor
- Compact enclosure
- Programmable status indicators

Imaging area
(actual size)



- Spectroscopy
- Star Tracking
- Medical Imaging


CCD Specifications

CCD	Kodak KAF-0261E
Array Size (pixels)	512 x 512
Pixel size	20 x 20 microns
Imaging area	10.24 x 10.24 mm (104.9 mm ²)
Imaging diagonal	14.48 mm
Linear Full Well (typ.)	200,000 e ⁻
Dynamic Range	>83 dB
QE @ 400 nm	29%
Peak QE (590 nm)	65%

For complete CCD specifications, including cosmetic grading,
see data sheet from manufacturer.




11760 Atwood Road, Suite 4 Auburn CA 95603 USA
Tel 530 888 0500 Fax 530 888 0540 www.ccd.com



PC Interface	USB 2.0
Max. cable length	5 meters between hubs; 5 hubs maximum (max. total of 30m)
Digital resolution	High gain output: 12 bits at 5 MHz and 16 bits at 1 MHz. Low Gain output: 12 bits at 2 MHz and 16 bits at 500 kHz
System Noise (typ.)	2 counts at 12 bits. 16 bits: 16 e ⁻ RMS (High gain); 33 e ⁻ RMS (Low gain)
Pixel Binning	1x1 to 10 x 512 on-chip
Exposure Time	10 milliseconds to 183 minutes (2.56 microsecond increments)
Image Sequencing	1-65535 image sequences under software control
Frame Sizes	Full frame, subframe, focus mode
Cooling	Thermoelectric cooler with forced air. Maximum cooling 50° C below ambient temperature
Temperature Stability	±0.1° C
Dark Current (typ.)	1 e ⁻ /pixel/sec (-30° C)
Camera Head	Standard: D1; Low profile: D5. Aluminum, hard blue and black anodized. 6" x 6" x 2.1" (15 x 15 x 6.25 cm). Weight: 3.1 lb. (1.4 kg)
Mounting	3.5" bolt circle, 8-32 thread. C-mount (1" 32 tpi thread). Optional Nikon or Canon lens mount.
Back focal distance	Standard: 0.69" (1.75 cm). Low profile: 0.46" (1.22 cm) [optical]
Operating Environment	Temperature: -22° to 27°C. Relative humidity 10 to 90% noncondensing
Cable length	Standard: 15 ft. (4.5m)
Power	40W maximum power with shutter open and cooling maximum. Power supplied by AC/DC "brick" supply with international AC input plug. Alternate 12V input for user's source.
Shutter	Standard: Vincent 25mm. Low profile: no shutter.
Remote Triggering	LVTTL input to camera allows exposure start within 25 microseconds of rising edge of trigger



CCD Sensitivity



11760 Atwood Road, Suite 4 Auburn CA 95603 USA
 Tel 530 888 0500 Fax 530 888 0540 www.ccd.com